





Baumform / Type	Classic Compact 90	Short Case 35	Quick Connect 90
			
Interface Connector	D-Sub, male 9-way	D-Sub, male 9-way	D-Sub, male 9-way
Service and program interface (PG)	D-Sub, female 9-way	D-Sub, female 9-way	D-Sub, female 9-way
Cable entry	2x 90° horizontal	2x 35° Outgoing cable	2x 90° horizontal
Cable diameter	5,5 ... 8,0 mm	8,0 mm	8,0 mm
Cross section of wire	Up to 1,0 mm	Up to 1,0 mm ²	0,64 mm ²
Cable termination	Screw terminals	Screw terminals	Slide switch technology
Data transmission rate	Max. 12 Mbit/s	Max. 12 Mbit/s	Max. 12 Mbit/s
Operating temperature	0°C ... - 60°C	0°C ... - 60°C	0°C ... + 60°C
Operating voltage	4,75 ... 5,25 V (DC)	4,75 ... 5,25 V (DC)	4,75 ... 5,25 V (DC)
Max. humidity	75 % (25°C)	75 % (25°C)	75 % (25°C)
Protection class	20 IP	20 IP	20 IP
Dimensions	68 x 43 x 17 mm	60 x 40 x 16 mm	72 x 40 x 17 mm
EMC	Screening by metallized housing	Screening by metallized housing	Screening by metallized housing
Pins	Pin 3 – Data B Pin 5 – GND Pin 6 – VP (+5V) Pin 8 – Data A	Pin 3 – Data B Pin 5 – GND Pin 6 – VP (+5V) Pin 8 – Data A	Pin 3 – Data B Pin 5 – GND Pin 6 – VP (+5V) Pin 8 – Data A
Weight	35 g (ohne PG) / 40 g (mit PG) 35 g (without PG) / 40 g (with PG)	35 g (ohne PG) / 40 g (mit PG) 35 g (without PG) / 40 g (with PG)	35 g (ohne PG) / 40 g (mit PG) 35 g (without PG) / 40 g (with PG)
Flammability housing	UL94 HB	UL94 V-0	UL94 V-0